
## Junttan PM 16 Driven Rig Information Sheet



| TECHNICAL DATA                |             |                 |
|-------------------------------|-------------|-----------------|
| Specification                 |             |                 |
| Hammer Type                   | HHK-3/4A    |                 |
| Hammer Weight                 | kg          | 6.100 or 7.200  |
| Hammer Stroke                 | mm          | Variable 0-1200 |
| Working Heights               |             |                 |
| Maximum Leader                | mm          | 21470           |
| Minimum Leader                | mm          | 19.750          |
| Maximum Pile Diameter         | mm          |                 |
| Maximum Pile Length           | m           | 14.0m           |
| Weights and Dimensions        |             |                 |
| Transport                     |             |                 |
| Transport width               | mm          | 3.180           |
| Transport height              | mm          | 3.620           |
| Transport length              | mm          | 15.600          |
| Transport weight 3&4 t hammer | ton         | 38.9 & 40.00/4t |
| Operating                     |             |                 |
| Operating width with 900 shoe | mm          | 4000 or 4100    |
| Operating height              | mm          | 21.470          |
| Operating weight              | ton         | 38.9 & 40.0     |
| Overall                       |             |                 |
| Overall length                | mm          | 7840            |
| Overall width                 | mm          | 4000 or 4100    |
| Track shoe width              | mm          | 900 or 1000     |
| Bearing pressure              | See GPL WPC |                 |

## Working Conditions 13720 4560 2400...3600 3860



**Transport Conditions** 

